

2010

Liqui-PREP™ Equipment & Accessories



Product: *Liqui-PREP™* L-500 Centrifuge

Features:

- ◆ Swing bucket rotor (equipped with brackets):
12 x 15 mL (max capacity)
optional rotors: 24 x 5 mL
24 x 10 mL
4 x 50 mL
- ◆ Digital speed control: max speed 2900xg (4200 rpm)
- ◆ Digital timer: 0-99min59sec
- ◆ Noise: <60dB(A)
- ◆ Weight: 14kg (30.86 lbs)
- ◆ Dimensions: 380x400x350mm ; 15 x 15.75 x 13.78 inches
- ◆ Electrical: 100V /60HZ 3A (Cat. No 50-5120)
220V /50Hz 3A (Cat. No. 50-5220)



Product: *Liqui-PREP™* L-530 Centrifuge

Features:

- ◆ Max Speed: 5300r/min
- ◆ Max RCF: 5010×g
- ◆ Max Capacity: 800ml (4×2×100ml)
- ◆ Time Range:0-99min
- ◆ Speed Accuracy: ±30r/min
- ◆ Power Supply: Ac220V 50Hz 5A (Cat. No. 50-6220)
- ◆ Noise: <65dB (A)
- ◆ Dimension: 470×560×380mm (L×W×H)
18.5 x 22.05 x 14.96 inches
- ◆ Weight: 40kg (88.18 lbs)
- ▶ Rotor Options;
 - std with 32 x 15 ml rotor
 - add additional rotor to P.O
 - microplate rotors are available



Product Number: *Liqui-PREP™* XH-B Vortex

Specifications:

- ◆ Oscillating Speed: 2600 rpm
- ◆ Electrical: 100V +/- 10%/60 Hz (Cat. No. 50-0120)
220V +/- 10% /50 Hz (Cat. No. 50-0220)
- ◆ Power Consumption: 12W
- ◆ Control modes: Continuous mode
- ◆ Weight: 3 kg (6.61 lbs)
- ◆ Dimensions: 23 x 19.5 x 23 cm (9.06 x 7.68 x 9.06 inches)



Product Number: 50-5000

Microscope slides: 50/box

Screened with 17 mm circle, Liqui-PREP and LGM International Inc. name.